

# M230i Wipe and Reverse Wipe

## Versatile, high speed labelling

The M-Series Wipe and Reverse Wipe **i-Tech** units offer high speed Print & Apply capabilities to suit a wide range of applications for box and product labelling.

The simple movement of the **M230i-WI00** and **M230i-WR100** is ideal for labelling moving products in a wide range of industries.



## Easy to operate - simple operation and unrivalled capability

- ◆ Clear monitoring & control with optional **TouchPanel** colour user interface
- ◆ Easy navigation and operation with intuitive **QuickStep** software
- ◆ Minimum downtime with tool-free magnetic printhead mounting system & expanding ribbon mandrels

## Lower Total Cost of Ownership – reduced cost and increased efficiency

- ◆ Increased printhead life
- ◆ Lower material wastage with full label coverage allowing optimum label size
- ◆ Increased uptime with fast consumable and print head changes

## Improved performance - sets the standard for efficiency

- ◆ 600m ribbon & label roll capacity within a compact footprint
- ◆ Increased print speed for reduced cycle times
- ◆ Robust design supports all mounting orientations
- ◆ Supply chain compliance with full GSI coding capability at high resolution including bar codes, text and graphics



## Benefits of Wipe / Reverse Wipe

- ◆ Standard Wipe or Reverse Wipe applicator
- ◆ Variable label lengths with Reverse Wipe
- ◆ High speed labelling
- ◆ Industrial robust design
- ◆ Easy and fast consumable changes
- ◆ Side, top or bottom labelling
- ◆ Left and right hand versions as standard



## Optional **QuickStep** User Interface

For effortless control and status reporting **QuickStep** is our unique, simplified operator interface that gets the printer into action quickly and simply. No complex menus or parameters, just enter the job and away you go.

- ◆ Quick access to favourite menus and settings via large user-friendly icons and customisable home screen.
- ◆ Easy, prompted input of data into label templates.
- ◆ Speed up changeovers and help eliminate coding selection errors with simplified Message Store and live WYSIWYG preview.



## WR100



## Technical Specification:

### M230i-WI100 & M230i-WR100

Print technologies:	Thermal Transfer
Print resolutions:	12 dots/mm (300dpi)
Typical speeds:	20-50 labels per min
Label sizes:	Up to 110 x 300mm
Label & ribbon lengths:	600m
Distance to product:	Up to 90mm
Pneumatics:	6 bar compressed air
Communication:	2 x RS232, 1 x USB 2.0, Ethernet
I/Os (configurable):	10 Inputs and 10 Outputs
User interface:	Graphical display with 25 languages
Overall Dimensions:	668 x 516 x 243mm (Printer & Applicator min) 668 x 858 x 314mm (Printer & Applicator max) 406 x 278 x 129mm (Controller - PCU)

Larger labels and longer stroke lengths are available - details on request